



# SDI 73DP

## PRODUCT DATA

## DAMPPROOFING

### **SDI 73DP CLIPPERSHIP NON-FIBRED EMULSION COATING**

**PRODUCT DESCRIPTION:** Clippership Non-Fibred Emulsion Coating meets ASTM-D-1227-87 Type III specifications. This material is an asphalt emulsion with

**BASIC USES:** Clippership Non-Fibred Emulsion Coating is used as protective coating for a variety of applications on asphalt, metal, and

**LIMITATIONS:** DO NOT ALLOW material to freeze. DO NOT THIN material.

**APPLICATION:** Clippership Non-Fibred Emulsion Coating must be applied to a surface that is free from all foreign matter. This material should remain dry until it has cured. This material can be applied by brush, squeegee, or spray equipment and should yield a coverage rate of 40 square feet

**STORAGE:** Clippership Non-Fibred Emulsion Coating must be kept from freezing.

**COMPOSITION:** Asphalt CAS 8052-42-4  
Water CAS 7732-18-5

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.