

1. **PRODUCT NAME**

Renew-Crete® Roll Coat Mix

"A Decorative Co-Polymer-Modified Overlay Coating"

2. **MANUFACTURER**

Renew-Crete Systems, Inc.
 2020 Murrell Rd. Rockledge, Fl. 32955
 PHONE (321) 636-8882
 TOLL FREE (888) 287-8962
 FAX (321) 636-7343

3. **PRODUCT DESCRIPTION**

Renew-Crete® Roll Coat is a one component, high performance blend of high quality Portland cement, modified Co-Polymers, and Iron Oxide Pigments. It is designed for maximum strength, flexibility, adhesion, abrasion resistance, and freeze/thaw resistance. Renew-Crete Systems uses all of the necessary ingredients and pre-blends them in a controlled environment. This ensures the proper ratios of co-polymer to cement, and cement to pigments are consistent. This promotes both product and color consistency saving you time on the job-site. This formulation may be used for many different decorative applications.

4. **PRODUCT USES**

Renew-Crete® Roll Coat Mix is widely used to restore color on existing decorative concrete surfaces. **Roll Coat** can be used on existing stamped concrete surface that has worn, or to unify new stamped areas that may have color inconsistencies. **Roll Coat** can be used to color any decorative concrete surface without changing the appearance of pattern and/or texture. **Roll Coat** is ideal for coloring:

Broom Textured finishes	Stamped Concrete	Commercial
Spray Textured finishes	Stamped Overlays	Industrial
May be Chemically Stained	Interior and exterior	Residential

5. **SURFACE PRPARARATION**

The concrete surface must be clean and free from all sealers, paints, grease, oil or any other contaminates. Thoroughly degrease and ash the concrete surface. Using 4 parts water and 1 part Muriatic Acid flood the surface using a broom to spread the solution evenly. Using a pressure washer completely wash the surface, making sure to rinse the surface clean. Allow the surface to dry before applying **Roll Coat**.

6. **MIXING**

Measure 2.5 Gallons of cool clean water, add 2 **Color Packs** and mix for 1 minute using a drill with a paddle mixer. Slowly add the **Roll Coat** to the water while mixing. Mix thoroughly for 2 minutes. The finished product should be the consistency of a thick paint.

7. **APPLICATION**

Lightly mist the concrete surface with cool clean water, Do Not Puddle. Using a heavy nap (1/2 or larger) apply the **Roll Coat** making sure to get an even application without roller marks. Recommended application is 2 coats, change direction between coats. It may be necessary to thin the product with a small amount of water if it thickens during application.

8. **ANTIQUING**

Stamped patterns may be antiqued after the **Roll Coat** has dried for a period of at least 24 hours using **Renew-Crete® Color Wash**.

9. **SEALING**

After the antiquing has dried completely, the surface should be sealed with 3 coats of **Renew-Crete® Hi-Gloss Sealer**. Wait 1 hour between coats, adding **Renew-Crete® Rhino-Grip** skid resistant additive if desired.

10. **COVERAGE**

1 container covers 400-600 Sq Ft