

# SDI STAMP SEAL PENETRATING

NON-YELLOWING, PENETRATING, ACRYLIC CONCRETE SEALER

## PRODUCT DESCRIPTION

**PENETRATING** is a non-yellowing, pure acrylic concrete sealer designed for all types of concrete. **PENETRATING** offers improved resistance to rain, the sun, freezing temperatures, stains, and other pollutants that sometimes can be hazardous to concrete. Applying **PENETRATING** to exposed aggregate will also help to eliminate loose pebbles and pre-mature wear. **PENETRATING** offers improved resistance to rain, sun, freezing temperatures, stains, and other pollutants that sometimes can be hazardous to concrete. **PENETRATING** can be considered an ultimate multi-use concrete sealer.

## BENEFITS/FEATURES

- ◆ Can be used as a means of dustproofing most concrete surfaces.
- ◆ Due to our 100% pure acrylic formula, this product will not yellow under ultraviolet exposure.
- ◆ Deep penetrating and ultra low viscosity formula allows for easy application through sprayers
- ◆ It's ease of use and it's medium gloss appearance makes this product a customer favorite.
- ◆ Low 400 VOC content allows for broader range of use across the country.

## RECOMMENDED APPLICATIONS

**2000 Supreme** is recommended for use on Stamped Concrete, Stenciled Concrete, Acid Stained Concrete, Overlaid Concrete, Exposed Aggregate Concrete, Broom Finish Concrete, and Trowel Finish Concrete. Other uses may be acceptable.

## TECHNICAL INFORMATION

Solids.....	25%	Wet Appearance.....	Clear to lightly cloudy
Drying Time.....	1 - 2 hours	Dry Appearance.....	Clear and Medium Gloss
Re-Coat Time.....	4 - 24 hours	VOC Content.....	<400 g/l
Foot Traffic.....	4 - 6 hours	Blush Resistance.....	Good
Wheel Traffic.....	24 - 48 hours	Solvent Resistance.....	Minimal
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	Excellent

## SPECIFICATIONS/COMPLIANCES

•• ASTM C 309, Type 1, Class A  
•• ASTM C-1315 Type 1, Class A

•• ASTM C 309, Type 1, Class B  
•• DRIED COATING IS USDA ACCEPTED

## APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First</u>	<u>Optional Second Coat</u>
New (unsealed) concrete	250-350 ft <sup>2</sup>	350-400 ft <sup>2</sup>
Old (sealed) concrete	350-400 ft <sup>2</sup>	350-400 ft <sup>2</sup>

\*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided.

## SHELF LIFE

**PENETRATING** has a shelf life of up to two years in it's original, sealed, unopened container.

## PACKAGING

**PENETRATING** is packaged in 1 gallon cans, 5 gallon pails, and 55 gallon drums.



**SEALANT DEPOT, INC.**

1100 Taylor's Ln. Phone: (856) 829-7325  
Cinnaminson, NJ 08077 Fax: (856) 829-0430

Visit us online at: [www.sealantdepot.com](http://www.sealantdepot.com)

VOC COMPLIANT SEALERS

PENETRATING