

# SDI SURFACE AID

## SOLVENT BASED ACRYLIC SEALER

### PRODUCT DESCRIPTION

**Surface Aid** is made up of a strong blend of aromatic and ketone solvents and surfactants. It is used to restore heavily coated existing solvent based acrylic sealers that have started to soften, fade, peel, crack, delaminate, and deteriorate. **Surface Aid** also clears up white spots or blushing due to moisture content issues. **Surface Aid** melts the heavily coated existing solvent based acrylic sealer, and helps restore the original appearance without adding more acrylic to allow the sealer to wear off naturally over time without stripping the existing bulk of the coating.

### BENEFITS/FEATURES

- ◆ Superior ability to fix excessively coated acrylic sealer issues as opposed to expensive coating stripping.
  - ◆ This product re-vitalizes the existing surface without adding more acrylic.
- ◆ Very fast drying time highly reduces the risk of trapped solvent or other types of moisture issues.
  - ◆ It's ultra low viscosity allows for easy spraying through an acetone resistant sprayer.

### RECOMMENDED APPLICATIONS

**Surface Aid** is recommended for use on heavily coated existing sealed surfaces where softening, fading, peeling, cracking, delamination, and deterioration has taken place and a new sealed look is desired without the need of additional acrylic.

### TECHNICAL INFORMATION

Solids.....	0%	Wet Appearance.....	Clear
Drying Time.....	30 min. - 1 hour	Dry Appearance.....	Clear
Re-Coat Time.....	4 - 24 hours	VOC Content.....	<100 g/l
Foot Traffic.....	4 - 6 hours	Blush Resistance.....	Superior
Wheel Traffic.....	24 - 48 hours	Solvent Resistance.....	n/a
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	n/a

\*\*\*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

### SPECIFICATIONS/COMPLIANCES

Not Applicable

### APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First</u>	<u>Optional Second Coat</u>
Old (sealed) concrete	100-200 ft <sup>2</sup>	100-200 ft <sup>2</sup>

\*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided.

### SHELF LIFE

**Surface Aid** has a shelf life of up to two years in it's original, sealed, unopened container.

### PACKAGING

**Surface Aid** is packaged in 1 gallon cans, 5 gallon pails, and 55 gallon drums.



SEALANT DEPOT, INC..  
1100 Taylor's Ln. Phone: (856) 829-7325  
Cinnaminson, NJ 08077 Fax: (856) 829-0430  
Visit us online at: [www.sealantdepot.com](http://www.sealantdepot.com)

MISCELLANEOUS PRODUCTS

SURFACE AID