

SDI Product Data Sheet

SKID-TEX

Skid-Tex is an exclusive, non-skid compound, specially formulated for easy mixing and application in all types of floor paints. Gives a durable non-skid safety coating to all types of interior and exterior surfaces. Applies with a paint roller or brush as easy as if applying regular paint. Helps prevent slips and falls. Skid-Tex will not change the color or the performance properties of the paint. Skid-Tex is ideal for use with: washrooms, floors, patios, marine use, pool decks, stairways, ramps, ladders, and walkways.

PROPERTIES:

Color:	Beige				
Weight:			Case	Case	Cubic Ft.
	<u>Item#</u>	<u>Size</u>	<u>Pack</u>	<u>Weight</u>	<u>Per Case</u>
	22516	1lb. Carton	6	7lbs.	.19
	22532	2lb. Carton	6	14lbs.	.43
	22242	1lb. Pail	12	15lbs.	.53

Coverage: See paint manufacturer's label.
Consistency: Granular Powder
Drying Time: See paint manufacturer's label.
Toxicity: N/A
Flammability: N/A
Hazardous Ingredients: N/A

DIRECTIONS:

SURFACE PREPARATION:

Follow paint manufacturer's directions for surface preparation.

MIXING:

In a clean, separate container, add SKID-TEX to the paint, in proportion of one pound to one gallon of paint. The same proportion for one quart of paint is ½ cup of SKID-TEX. More or less may be added for a rougher or finer surface. Stir thoroughly, and for best results, let mix soak for at least 30 minutes before applying. Stir occasionally to insure good distribution of the mix.

APPLICATION:

Follow paint manufacturer's directions for paint application. Use either a brush or roller. If two coats of paint are used, SKID-TEX may be used in both coats, or use in the first coat only, and apply a second paint topcoat. For high-gloss finishes, use SKID-TEX in the first coat only, then apply a high-gloss topcoat.

CLEAN UP:

Follow paint manufacturer's directions for clean up.

CAUTIONS:

Keep out of reach of children. Do not take internally. If ingested, drink plenty of water and get medical attention. In case of eye contact, flush with water for 15 minutes and get medical attention. On skin, wash with soap and water.



SEALANT DEPOT, INC.

1100 Taylor's Ln. Phone: (856) 829-7325
Cinnaminson, NJ 08077 Fax: (856) 829-0430
Visit us online at: www.sealantdepot.com