

SDI XYLENE

XYLENE

CLEANING PRODUCTS

XYLENE

PRODUCT DESCRIPTION

SDI Xylene is used in various aspects of industry. *Xylene*, is used in the paint and coatings manufacturing process. These solvents can be used for many various reasons such as paint and coating clean-up for tools and accessories, paint thinning, coating re-emulsification for purpose of fixing faulty applications or conditions, etc.

BENEFITS/FEATURES

- ◆ Superior cleaning capabilities and re-emulsification properties of solvent based coatings.

RECOMMENDED APPLICATIONS

Applications Vary

TECHNICAL INFORMATION

Solids.....	0%	Wet Appearance.....	Clear
Drying Time.....	Refer to Directions	Dry Appearance.....	n/a
Re-Coat Time.....	Refer to Directions	VOC Content.....	Varies
Foot Traffic.....	Refer to Directions	Blush Resistance.....	n/a
Wheel Traffic.....	Refer to Directions	Solvent Resistance.....	n/a
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	n/a

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

Not Applicable

APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First</u>	<u>Optional Second Coat</u>
Varies	Varies	1/2

*Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.

SHELF LIFE

SDI Xylene have a shelf life of one-two years in it's original, sealed, unopened container.

PACKAGING

SDI Xylene are packaged and stocked in 1 gallon cans, 5 gallon pails, and 55 gallon drums



SEALANT DEPOT, INC.
1100 Taylor's Ln. Phone: (856) 829-7325
Cinnaminson, NJ 08077 Fax: (856) 829-0430
Visit us online at: www.sealantdepot.com